



**RFID Interoperability** 

## **Toshiba Tec Corporation Printer Summary Report**

Printer	
Manufacturer	Toshiba Tec Corporation
Model, Family	B-SX5T-TS22-QM-R (B-SX4/5 Series)
Configuration Tested	Europe
GSRN of the Printer	950110126000001589
Name/ GSRN of the	TRW-EUM-01
reader module	950110126000001541
Frequency Bands	862-870 MHz 🛛 902 – 928 MHz 🗆 950 – 956 MHz 🗆
*Tested Range:	1 meter
Notes	Models in this product family, utilizing the identical reader module, may be as interoperable as the tested printer. See printer manufacturer for details.

## IC

Name/GSRN of Certified IC	Impinj Monza 2 Tag IC 950110126000000520
Inlay Used	Rafsec Gen2 Short Dipole
Frequency Bands	862-870 MHz 🛛 902 – 928 MHz 🖂 950 – 956 MHz 🖂
*Tested Range:	1 meter
Notes	Inlay configurations that utilize the identical certified IC may be as interoperable as the tested inlay. See printer manufacturer for selection of inlays for this IC.

Name/GSRN of Certified IC	NXP Tag IC 95011012600000537
Inlay Used	Rafsec Gen2 Short Dipole
Frequency Bands	862-870 MHz 🛛 902 – 928 MHz 🖂 950 – 956 MHz 🖂
*Tested Range:	1 meter
Notes	Inlay configurations that utilize the identical certified IC may be as interoperable as the tested inlay. See printer manufacturer for selection of inlays for this IC.

\*The distance between the written label and QE reader antenna IC – Integrated Circuit